



User Guide for Everbrite™ Coating: ALUMINIUM

Email: branden@restoreandprotectsa.co.za

Website: www.restoreandprotectsa.co.za

HOW TO REFURBISH OXIDIZED, FADED OR STAINED ANODIZED ALUMINIUM, POWDER COATED ALUMINIUM OR PAINTED ALUMINIUM

Anodized aluminium extrusions can fade and oxidize. Aluminium can get ugly pits from salt corrosion if located near the ocean. Faded or chalky window frames or aluminium joinery can ruin the appearance of your home or building. Everbrite™ is a clear protective coating that will restore the colour and lustre on dull, faded or stained aluminium and will protect from oxidation, corrosion, salts and other damaging elements. This procedure can also be used to refurbish faded or oxidized aluminium curtain wall, patio furniture, window frames, store fronts or other oxidized aluminium.

1. PREPARATION

1. Use an approved scrubber pad. A blue or white ScotchBrite pad can also be used.
2. Rinse the aluminium with water.
3. Use the Prep Pad and Aluminium Cleaner to scrub gently with the grain to remove chalk, oxidation, dirt and any mould etc.
4. Rinse with fresh water until the water sheets off of the metal. Do NOT let the cleaner dry on the surface; it will be more difficult to remove.
How the aluminium looks when it is clean and wet is how it will look once it is coated so if you see streaking or areas that are not clean **STOP** and re-clean.
Do not coat over oxidation or dirt.
5. Wipe dry with microfiber cloth. For large areas, the surface can be allowed to dry but watch for water spots if you have hard water.

2. COATING APPLICATION

Do not apply the coating if the metal is hot or in the direct sun over 29°C

Materials needed:

- Everbrite™ protective coating.
- Applicator- clear-coat applicator (included with your kit) or a soft paint brush that is solvent rated.
- Metal Application pan- a metal paint pan or disposable mini loaf pans work well.
- Personal Protection: Nitrile or chemical protective gloves to protect your hands. (Rubber gloves will get sticky)



User Guide for Everbrite™ Coating: ALUMINIUM

Email: branden@restoreandprotectsa.co.za

Website: www.restoreandprotectsa.co.za

1. Pour a small amount of Everbrite™ into a clean, dry metal container. Do not use plastic. DO NOT DILUTE EVERBRITE COATINGS WITH ANYTHING ELSE.
2. Dip the applicator pad into the Everbrite™. Applicator should be completely wet but should not be dripping.
3. Apply the Everbrite™ to the surface, letting the applicator glide across the surface. Do NOT press hard. The applicator should glide smoothly, when it starts sticking, dip applicator in Everbrite™ again. If you get drips or runs on the surface, simply wipe them out with your applicator before the coating dries.
4. Once you apply the coating, leave it alone and let the coating dry. It will self-level as it dries. The coating will dry to touch in about 15-40 minutes depending on the temperature & humidity.
5. Any missed areas or thin areas can be touched up after the coating is dry to touch. Don't try to fix the coating as it dries, let it dry and then reapply.

*****If you see streaks, it is generally caused by not having the coating evenly distributed throughout the applicator or by pressing too hard and not leaving enough coating on the surface.*****

DANGER: HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: In case of eye contact, flush thoroughly with plenty of water for 15 minutes and get medical attention. For skin contact, wash with soap & water. In case of respiratory difficulty, provide fresh air & call a Doctor.

NOTICE: Reports have associated repeated & prolonged over-exposure to solvents with damage to health. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CAUTION: Combustible liquid. Material does not sustain combustion. Do not smoke or use near flame. Use with adequate ventilation. Avoid continuous breathing vapour or spray mist. Avoid prolonged contact with skin. Wear gloves & eye protection. Store in a cool, dry place.